Line of Stop 11 8000 S OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER $\frac{21}{12-03-02}$ TOWNSHIP $\frac{14}{1-11-07}$ RANGE _ SECTION _ /e / Wilcoxen PARTY CHIEF: __ Harv CREW: _ TYPE OF MARKER: Harrison Fd Mitthoefer/ METHOD OF ESTABLISHMENT: ____County: 10-26-98 IN. S.P.C. E ZONE NAD '83 NAME: 14052101 N: 489014.8852(m) 72231.6033(m) 4. E: Mitthoefer Line of Stop 11 Rd 8000 S Address 8025 1.

Original post set 1820 by Hendricks with witnesses: 20" beech N 21 links, 15" beech N 5 W 20 links per Marion County Atlas pg. 13. Mayhew 10, 15 & 16-1858 called stone found per Franklin Township Legal Survey Book pg. 43. 7-8-64 NE 20-14-5 called pipe over stone. 6-12-80 called pipe over stone. Excavated 7-25-88 stone found 6" down with 1" iron pipe angled over stone. Harrison set 7-25-88. Raised to surface 9-12-94. Re-tied 10-26-98 by Kiste,

Re-tied 12-03-02 by Wilcoxen. 14052101

		14052101
REF.	DISTANCE	DESCRIPTION
1.	25.24	PK nail W PwP#52-801 C
2.	2689.38	Due S to W Q corner (Cut 'x' in 1 1/4" steel pin, fd)
3.	56.51	Mag nail w/brass washer SE PwP#44-801 8"up
4.	93.25'	Small PK nail E PwP#79-801 B 12"up